


DOOBONING.



TECHNICAL DATA SHEET

Polylizer 120

Description

Polylizer-120 is one of DOOBON's synthetic hydrotalcite series and can be used for stabilizing PVC. It shows well-performance in Ca-Zn stabilizer which is an environmentally friendly, non-toxic and heavy metal free. Polylizer-120 also has been shown effective performance for compounding in green house master batch application.

Structure Mg₄Al₂(OH)₁₂CO₃ 3H₂O

Appearance Fine, white powder

Specifications

Particle Size d(0.5) > 10 μm	μm % (Vol)	0.2 ~ 0.5 0.0
Heavy Metals	ppm	Max 10
Molar Ratio MgO/Al ₂ O ₃	-	3.5~5.0
Drying Loss(105°C/1hr)	%	Max 0.5
Na Content(Na)	ppm	Max 250
Bulk Density	g/ml	0.3 ~ 0.5
Surface Area(BET)	m²/g	8~12

Application

- Whole area of PVC application related with Ca-Zn Heat Stabilizer.
- PE insulation film for green house.

Handling

Packaging Paper Bags, PE inner liner, 20 kg net

Storage Cool, Dry and well ventilated area at room temperature

The information supplied is presented in good faith and has been derived from sources believed to be reliable. Since conditions of use are beyond our control, all risks are assumed by the user. No representation is expressed or implied, and nothing here in shall be construed as permission or recommendation to practice a patented invention without a license.



^{*} For additional handling and toxicological information, consult the DOOBON Material Safety Data Sheet.



Hydrotalcite for PVC Heat Stabilizer

TECHNICAL DATA SHEET

Polylizer 120


Hydrotalcite is...?

Inactivation of Hydrotalcite to anion materials

MCI_x(anion materials)



 $Mg_1-xAl_x(OH)_2(CO_3)_{x/2}$. nH_2O (Hydrotalcite)













Residual Catalyst make

- 1. reducing heat stability
- 2. a mold corrosion of mold surface
- 3. high processing pressure and fish-eye

Application Fields of Hydrotalcite

Film insulator Maintain the thermal insulation ability by adding 1-20 part in ratio of resin

agriculture film for PE, PP, EVA etc.

Fume capture For assisting flame retardant. When it is added to polymer, prevents and

absorb fume of halogen from flame retardants.

Heat stabilizer Heat stabilizer for PVC, PVDC, Heat and ultraviolet resistant.

Acid acceptor Halogen containing rubber, pharmacy, medical treatment and textile.

DOOBON INC

59, Hwangtanli-gil, Gangnae-myeon, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, Republic of KOREA, 28174 TEL: +82-43-235-2307 FAX: +82-43-235-2314 http://www.doobon.co.kr





