


DOOBONING.



TECHNICAL DATA SHEET

Polylizer 121

Description

DOOBON's synthetic hydrotalcite, Polylizer-121, is commonly used for stabilizing PVC. It shows well-performance in Ca-Zn stabilizer which is an environmentally friendly, non-toxic and heavy metal free. Polylizer-121 has been developed in accordance with market requirements and satisfaction of our customer needs.

Structure Mg₃ZnAl₂(OH)₁₂CO₃ 3H₂O

Appearance Fine, white powder

Specifications

Moisture	%	Max 0.5
Molar Ratio MgO/Al₂O₃	-	2.9 ~ 3.5
Molar Ratio ZnO/Al ₂ O₃	-	0.9 ~ 1.1
pH(2% Ethanol)	-	8.0 ~ 9.5
Bulk Density	g/ml	$0.3 \sim 0.5$
Metal Contents	ppm	Max 10
Particle Size < 1 μm	% (Vol)	Min 70.0
> 5 <i>µ</i> m	% (Vol)	Max 0.5

Application

- Whole area of PVC application related with Ca-Zn Heat Stabilizer.

Handling

Packaging Paper Bags, PE inner liner, 20 kg net

Storage Cool, Dry and well ventilated area at room temperature

The information supplied is presented in good faith and has been derived from sources believed to be reliable. Since conditions of use are beyond our control, all risks are assumed by the user. No representation is expressed or implied, and nothing here in shall be construed as permission or recommendation to practice a patented invention without a license.



^{*} For additional handling and toxicological information, consult the DOOBON Material Safety Data Sheet.



Hydrotalcite for PVC Heat Stabilizer

TECHNICAL DATA SHEET

Polylizer 121

Hydrotalcite is...?


Inactivation of Hydrotalcite to anion materials

MCI_x(anion materials)



 $Mg_1-xAl_x(OH)_2(CO_3)_{x/2}$. nH_2O (Hydrotalcite)
















OH

Residual Catalyst make

- 1. reducing heat stability
- 2. a mold corrosion of mold surface
- 3. high processing pressure and fish-eye

Application Fields of Hydrotalcite

Film insulator Maintain the thermal insulation ability by adding 1-20 part in ratio of resin

agriculture film for PE, PP, EVA etc.

Fume capture For assisting flame retardant. When it is added to polymer, prevents and

absorb fume of halogen from flame retardants.

Heat stabilizer Heat stabilizer for PVC, PVDC, Heat and ultraviolet resistant.

Acid acceptor Halogen containing rubber, pharmacy, medical treatment and textile.

59, Hwangtanli-gil, Gangnae-myeon, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, Republic of KOREA, 28174 TEL: +82-43-235-2307 FAX: +82-43-235-2314 http://www.doobon.co.kr

